Epson EB-XQ2030B



Marke : Epson

Artikel-Code: V11HC01880

Produktname : EB-XQ2030B

Epson EB-XQ2030B. Projektorhelligkeit: 30000 ANSI Lumen, Projektionstechnologie: 3LCD, native Auflösung des Projektors: UHD 4K (3840x2160). Typ der Lichtquelle: Laser, Lebensdauer der Lichtquelle: 20000 h, Lebensdauer der Lichtquelle (ökonomischer Modus): 30000 h. Fokus: Motorisiert, Brennweitenbereich: Varies by lens, Projektionsverhältnis: 0.34 - 11.00:1, Varies by lens. Videoverarbeitung: 10 Bit, Video-Farbmodi: BT.709, Kino, DICOM Simulationsmodus, Dynamisch, Multi-projection, Natürlich/Natur, Präsentation. Serielle Schnittstelle: RS-232C, Typ Serviceport: USB Typ-B



Projektor	
Kontrastverhältnis (dynamisch)	5000000:1
Projektorhelligkeit *	30000 ANSI Lumen
Projektionstechnologie *	3LCD
native Auflösung des Projektors *	UHD 4K (3840x2160)
Kontrastverhältnis *	3000:1
Natives Seitenverhältnis *	16:9
Anzahl der Farben	1,07 Milliarden Farben
Projektorhelligkeit (Energiesparmodus)	21000 ANSI Lumen
Trapezkorrektur, horizontal	±30°
Trapezkorrektur, vertikal	±45°
Matrix Größe	2,64 cm (1.04")
Wärmeableitung	7106 BTU/h

Lichtquelle	
Typ der Lichtquelle *	Laser
Lebensdauer der Lichtquelle *	20000 h
Lebensdauer der Lichtquelle (ökonomischer Modus)	30000 h

Objektiv	
Fokus *	Motorisiert
Brennweitenbereich	Varies by lens
Zoom-Fähigkeit	✔
Projektionsverhältnis	0.34 - 11.00:1, Varies by lens
Wechselobjektiv	✔

Video	
Analoges Signalformatsystem *	Nicht unterstützt
Full-HD *	✔
3D *	✘
Videoverarbeitung	10 Bit
Video-Farbmodi	BT.709, Kino, DICOM Simulationsmodus, Dynamisch, Multi-projection, Natürlich/Natur, Präsentation

Merkmale	
Technologie mit hohem Dynamikbereich (HDR)	High Dynamic Range 10 (HDR10), Hybrid Log-Gamma (HLG)
Passwortschutz	✔

Design	
Produktfarbe *	Schwarz
Platzierung	Zimmerdecke, Flur, Flying frame
Kabelsperre-Slot	✔
Slot-Typ Kabelsperre	Kensington

Bildschirm	
Eingebautes Display *	✘

Energie	
Energiequelle *	AC
Stromverbrauch (Standardbetrieb) *	1895 W
Verbrauch (Energiesparmodus)	1180 W
AC Eingangsspannung	100 - 240 V
AC Eingangsfrequenz	50 - 60 Hz

Betriebsbedingungen	
Temperaturbereich bei Lagerung	-10 - 60 °C
Relative Luftfeuchtigkeit in Betrieb	20 - 80%
Luftfeuchtigkeit bei Lagerung	10 - 90%

Gewicht und Abmessungen	
Breite	620 mm
Tiefe	530 mm
Höhe	205 mm
Gewicht *	34,4 kg
Verpackungsbreite	760 mm
Verpackungstiefe	840 mm
Verpackungshöhe	340 mm
Paketgewicht	45 kg

Lieferumfang	
Fernbedienung enthalten *	✔

Anschlüsse und Schnittstellen	
HDBaseT-Port	✔
Typ Serviceport	USB Typ-B
Menge USB 2.0-Anschlüsse	2
Serielle Schnittstelle *	RS-232C
Anzahl HDMI-Anschlüsse *	2
DVI Anschluss *	✘

Netzwerk	
Smart-TV *	✘
Ethernet/LAN *	✔
Ethernet LAN Datentransferraten	10,100 Mbit/s
WLAN *	✔
WLAN-Standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)

Speichermedium	
Integrierter Kartenleser *	✘

Merkmale	
Geräuschpegel (Energiesparmodus)	39 dB
Geräuschpegel *	48 dB
High Dynamic Range Video (HDR) Unterstützung	✔

Lieferumfang	
Mitgelieferte Software	Epson Creative Projection, Epson Projector Config Tool, Epson Projector Content Manager, Epson Projector Management, Epson Projector Professional Tool

Technische Details	
Duplex Scan-Geschwindigkeit (Farbe)	21:9 aspect ratio support, A/V mute, Auto Power On, Auto source search, CEC compatible, Daisy chain Multi-Projection, Direct Power on/off, Edge Blending, Frame interpolation, Freeze image, Horizontal and vertical keystone correction, Integrated camera for image calibration, Lens position memory, Long light source life, OSD copy function, Point correction, Quick Corner, Schedule Function, Web Control, Wireless LAN capable
Stromverbauch	1,895 Watt (Normal On-Mode), 1,180 Watt (Eco On-Mode), 2,090 Watt (Normal Peak-mode), 1,546 Watt (Eco Peak-Mode), 1 Watt (Energy saving standby)

Logistikdaten	
Menge pro Packung	1 Stück(e)

Sonstige Funktionen	
Schnittstelle	USB 2.0 (2x), USB 2.0 Type B (Service Only), RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n, HDMI in (2x), HDMI out, HDBaseT, Jack plug out, Near Field Communication (NFC), 12G SDI Input, 12G SDI Output, USB content playback, Remote
Bedienfeld	1.04 inch with C2 Fine
Unterstützte Netzwerkprotokolle	HTTPS, SNMP, ESC/VP.net, PJLink
Sicherheit Eigenschaften	Kensington lock, Security bar, Control panel lock, Padlock, Security cable hole, Wireless LAN security, Password protection

8715946746968

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 27-SEP-2026. Prints or copies of Information are only valid on the printed Publication date